



THE GENESIS LINE OF TLD DOSIMETERS

The cool look in radiation monitoring

The Dosimetry Services Division offers its line of Genesis TLD dosimeters. The Genesis line offers improved performance and superior user factors.

Both the Genesis and Genesis Ultra TLDs respond accurately to beta, gamma, X-ray and neutron radiation. The response of each element is corrected by the application of its own unique element correction factor. Both TLDs allow for the reporting of deep, lens of eye and shallow doses.

Unlike other TLD products, the Genesis Ultra TLD has virtually no fading characteristics. Due to the increase in signal response a minimum reportable dose (MRD) as low as 0.01 mSv is available, compared to the 0.10 mSv MRD of other TLD products.

FEATURES

Genesis TLD

- Wear periods from one week to one year
- Permanently bar-coded for user identification and tracking
- Whole-body, wrist and area monitoring configurations
- Provides thermal, intermediate and fast neutron dosimetry capability
- Improved label with larger fonts and wear locations
- Enhanced ergonomics with redesigned clip

Genesis Ultra TLD

- Virtually no fade
- Lower MRD available on request
- Wear periods from one week to one year
- Permanently bar-coded for user identification and tracking
- Whole-body, wrist and area monitoring configurations
- Provides thermal, intermediate and fast neutron dosimetry capability
- Improved label with larger fonts and wear locations
- Enhanced ergonomics with redesigned clip

APPLICATIONS

- Any occupational worker with potential exposure to gamma, X-ray, beta and/or neutron radiation.
- Nuclear medicine facilities, imaging centers, research diagnostic centers and all employees with potential exposure to gamma, X-ray and beta.
- Nuclear power plant workers, research laboratories, hospitals, universities and industrial applications.



dosimetry services

A Mirion Technologies Division

Featuring:



TECHNICAL SPECIFICATION

| | | |
|--|--|--|
| Badge Name | Genesis TLD Dosimeter | Genesis Ultra TLD Dosimeter |
| Badge Type | 16 DB= TLD 760 15 DB= TLD 760 with CR39 25 DB= TLD 760 with ¹¹⁵ In* and CR39 26 DB= TLD 760 with ¹¹⁵ In* | 36= TLD MCP 35= TLD MCP with CR39 |
| Description | 4 element Harshaw TLD (³ LiF:Mg, Ti [TLD700] and ¹ LiF:Mg, Ti [TLD600]) | 4 element Harshaw TLD (³ LiF:Mg, Cu, P [TLD700H] and ¹ LiF:Mg, Cu, P [TLD600H]) |
| Manufacturer | TLD: Thermo Electron RMP CR39: PPG | TLD: Thermo Electron RMP CR39: PPG |
| Accreditations/Approvals/Licenses | NVLAP (Code: 100555-0) HSE (United Kingdom) | NVLAP (Code: 100555-0) HSE (United Kingdom) DoELAP*** |
| Holder Type | Genesis | Genesis |
| Wear Location | Area, equipment, collar, lower left extremity, lower-right extremity, non-personal use, non-specific extremity, upper-left extremity, unknown, upper-right extremity, whole body | Area, equipment, collar, lower left extremity, lower-right extremity, non-personal use, non-specific extremity, upper-left extremity, unknown, upper-right extremity, whole body |
| Minimum Reportable Dose | 0.10 mSv | 0.01 mSv |
| Useful Dose Range | 0.10 mSv - 10 Gy | 0.01 mSv - 10 Gy |
| Energy Response | Beta (MAX) 0.766 MeV - 5 MeV Photon 5 keV - 6 MeV Neutron (TLD): Thermal - 6 MeV Neutron (CR39): 200 keV - 6 MeV** | Beta (MAX) 0.766 MeV - 5 MeV Photon 5 keV - 6 MeV Neutron (TLD): Thermal - 6 MeV Neutron (CR39): 200 keV - 6 MeV ** |

*Not accredited for personnel monitoring

**Neutron energies up to 20 MeV with CR39 and special calibration.

***DoELAP accreditation only applies to the Genesis Ultra with CR39

© Copyright 2008, All rights reserved. For trademark and registered trademark information.



Radiation Protection Services Limited
PO Box 79128
Avonhead
Christchurch 8446
Phone: 0508-723-776
Email: pds@radpro.co.nz
Web: http://www.radpro.co.nz

